



Nuts



Thread	RH or LH	Hex Nuts	Lock Nuts	Cap Nuts
1/4-28	RH LH	11HN8R 11HN8L	11HLN8R 11HLN8L	11HCN8R
5/16-24	RH LH	11HN10R 11HN10L	11HLN10R 11HLN10L	11HCN10R
3/8-24	RH LH	11HN12R 11HN12L	11HLN12R 11HLN12L	11HCN12R

Washer



Thread	Washers	Fender Washers
1/4	11HW8	11HFW8
5/16	11HW10	11HFW10
3/8	11HW12	11HFW12

Cap Screws

Stainless steel socket-head screws for mounting Adjust-A-Jaw® and Adjust-A-Body™ with Threaded Eye Tensioners and Ultra-tec® Fixed Jaws.



Cap Screws		
Thread	Used with hardware for cable diameters	Part No.
1/4-28	1/8", 3/16"	11HCS8
3/8-24	1/4", 5/16", 3/8"	11HCS12

Adjust-A-Ball (without counter bore)

Adjust-A-Balls are used with either our CSTS or threaded studs for angle compensation. These half round balls allow for the cable to swivel to any angle automatically. Simply drill the proper hole and the ball will adjust to the angled position as the cable is tensioned.

Adjust-A-balls will fit up to 1/4" cable. Holes in the outside of the end posts must be drilled to 11/16". If using a flat bar as your end post, you counter sink the hole to a 11/16" diameter.



Adjust-A-Ball (without counter bore)		
Ball Size (s)	Hole Size (t)	Part #
3/4"	25/64"	10HAB102

Adjust-A-Ball (with counter bore)

Adjust-A-Balls are used with our termination studs for stair angle compensation. These half round balls allow for the cable to swivel to any angle automatically. Simply drill the proper hole and the ball will adjust to the angled position as the cable is tensioned.

Adjust-A-balls will fit up to 1/4" cable. Holes in the outside of the end posts must be drilled to 11/16". If using a flat bar as your end post, you counter sink the hole to an 11/16" diameter



Adjust-A-Ball (with counter bore)		
Ball Size (s)	Hole Size (t)	Part #
3/4"	25/64"	10HAB101

Angle Washers

Angle washers are used with our CSTS, Threaded Stud, Termination Stud or Top Hat Systems for the standard 30° angle compensation of horizontal stair runs.



30° Angle Washers		
O.D.	I.D.	Part #
1/2"	1/4"	40HAW0830
1/2"	3/8"	40HAW1230
5/8"	1/2"	40HAW1630

Tubular Turnbuckle Bodies
316 grade stainless steel



Tubular Turnbuckle Bodies		
Thread Size	Body Length	Part No.
10-32	2-1/4"	10F6TBC2
10-32	3-1/2"	10F6TBC
1/4-28	2-3/4"	10F8TBC2
1/4-28	4-1/2"	10F8TBC
5/16-24	5"	10F10TBC
3/8-24	5-1/2"	10F12TBC
1/2-20	6-1/2"	10F16TBC
5/8-18	8-1/4"	10F20TBC
3/4-16	9-3/4"	10F24TBC